
Product Data sheet

Sensors and Actuator


- Product description- M12 Male Straight D Code to RJ45 Male Straight Pur Shielded Green Cable
- MPN-241245-9696-40948-814-XXXX-Gn
- Serie- M12 to RJ45 Cordset


Illustration







-Colour customization available based on MOQ









Product may differ from image

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZLFactory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Sensors and Actuator

Technical Data	
Operating voltage	Max. 60 V DC*
Rated Surge Voltage	1.0 kV
Operating current per contact AMP	Max. 1.5 A (20°C)
Connection type head A	M12 D Code, Male Straight Shielded connector 4-pin.
Connection type head B	RJ45, Male Straight. Shielded connector 8-pin.
Transfer parameters	Cat 5e
Transfer rate	100 Mbit/s
Locking of ports	Screw threaded
Protection	IP67, IP68, IP69.
Mechanical Life-cycle	Min. 100 Mating cycle
Housing Material	TPU, Black
Material Group	IEC 60664-1, Category |
Locking nut material	Nickel plated
Tightening torque	0.4 Nm

General Data	
Standards	IEC 61076-2-114(M8), IEC 60603-7(RJ45)
Mounting method	Inserted, tightened.
Contact Material	CuSn, Gold plated
Material (contact surface)	Au
Pollution Degree	3
Overvoltage Category	|||
Flammability Rating according to UL 94	V0
Temperature range	-25…. +105°C* (depending on Cable)

Cable Data	
Cable Type	CAT 6A PUR Shielded
Approval (cable)	UL, cULus, CE conformity, RoHS
Diameter (core)	8*0.14 mm².
AWG	similar to AWG 22
Material (wire isolation)	PE.

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZLFactory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Sensors and Actuator

Shore hardness (wire insulation)	70±5 D
Material property (wire isolation)	CFC-, Halogen-, cadmium-, silicone- and lead-free.
Colour/numbering of wires	White/Orange, Orange, White/Green, Blue, White/Blue, Green, White/ Brown, Brown
Stranding combination	4 wires twisted
Shield	Yes
Shielding	Tin Braided
Optical shield covering	Min 80%
Material (jacket)	PUR (UL/CSA)
Outer-Ø (jacket)	6.2mm ±0.2mm
Colour (jacket)	Green, similar RAL6018
Material properties (outer surface)	CFC-, Halogen-, cadmium-, silicone- and ad-free.
Shore hardness (outer surface)	75±5 D
Material (conductor)	Tinned Stranded Copper
Chemical resistance	good resistance to oil, gasoline and chemicals (EN 60811-404)
Thermal resistance	According to IEC 60332-2-2
Nominal voltage	300 V AC
Temperature range (fixed)	-40...+80 °C, (+105 °C. at max. 10 000 operating hours)
Temperature range (mobile)	-25...+80 °C, (+105 °C. at max. 10 000 operating hours)
Bend radius (fixed)	5× outer Ø
Bend radius (moving)	10× outer Ø
No. of bending cycles (C-track)	5 Mio. (25 °C)
No. of Torsion cycles (C-track)	5 Mio. Cycles

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZLFactory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Sensors and Actuator

Approvals
UL
CE
cULus
RoHS

241245-9696-40948-814-XXXX-Gn	
24	Series
12	M12 Connector
45	RJ45 Connector
96	Male Straight (M12)
96	Male Straight (RJ45)
4	D code
09	CAT6A PUR shielded
4	4 Pole (M12 Male Connector)
8	8 Pole (RJ45 Connector)
8	8 Core
14	0.14 mm^2 (Core size)
XXXX	As per customer requirement
Gn	Green Cable

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZLFactory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.