
# Product Data Sheet

## Sensors and Actuator


- Product description- M8 Female Angled A Code 4 Pin Pvc Shielded 3x0.34 Black
- 248-67-144-334-XXXX
- Series –M8 A coded


## Illustration




**-Colour customization available based on MOQ**




Product may differ from image



The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

# Product Data Sheet

## Sensors and Actuator

| Technical Data | |
|---|---|
| **Operating voltage** | 300V AC/DC* |
| **Rated Surge Voltage** | 1.5 kV |
| **Operating current per contact AMP** | Max. 4 A |
| **Connection type head A** | Female connector, M8, 4-pin, 90° Angle, A coded |
| **Connection type head B** | Open end |
| **Protection** | IP67, IP68, IP69 |
| **Housing Material** | TPU |
| **Locking nut material** | Brass, Nickel plated |
| **LED display** | No |
| **Connector colour** | Black |
| **Tightening torque** | 0.4 Nm |

| Electrical Data | |
|---|---|
| **Overvoltage category** | II |
| **Contact resistance** | ≤ 5 mΩ |
| **Insulation resistance** | ≥ 100 mΩ |
| **Test voltage** | ≥ 3000 V |
| **Conductor material** | Bare Cu litz wires |
| **Max. conductor resistance** | Max. 78 Ω/km (at 20 °c) |
| **Nominal voltage** | ≤ 300 v |

| Mechanical Data | |
|---|---|
| **Insertion/withdrawal cycles** | ≥ 100 |

| Product properties | |
|---|---|
| **Application** | Actuator-sensor, gigabit ethernet & Profibus |
| **Partly UV-resistant** | in accordance with DIN EN ISO 4892-2-A |
| **Flammability rating According to UL 94** | HB |



The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

# Product Data Sheet

## Sensors and Actuator

| General Data | |
|---|---|
| **Standards** | IEC-61076-2-101 (M12) |
| **Mounting method** | Inserted, tightened. |
| **Pin Contact** | CuZn |
| **Housing contact** | CuSn |
| **Material (contact surface)** | Au |
| **Pollution Degree** | 3 |
| **Stripping length (jacket)** | 20 mm (If required) |
| **Temperature range** | -25…..+105°C |

| Cable Data | |
|---|---|
| **Cable Type** | PVC |
| **Cable weight** | 53 g/m |
| **Diameter (core)** | 3*0.34 mm². |
| **AWG** | similar to AWG 22 |
| **Material (wire isolation)** | PVC |
| **Material property (wire isolation)** | CFC-, cadmium-, silicone- and lead-free |
| **Colour/numbering of wires** | Brown, Blue, Black |
| **Stranding combination** | 3 wires twisted |
| **Shield** | Yes |
| **Shielding** | Tin braided |
| **Optical shield covering** | Min 85% |
| **Material (jacket)** | PVC |
| **Outer-Ø (jacket)** | 5.00 ±0.2mm/6.20 ±0.2mm |
| **Colour (jacket)** | Black |
| **Chemical resistance** | good resistance to oil, gasoline and chemicals (EN 60811-404) |
| **Thermal resistance** | flame retardant UL 1581 Section 1090 (H), CSA FT2 / IEC 60332-2-2 |
| **Temperature range (fixed)** | -40...+80 °C, (+105 °C. at max. 10 000 operating hours) |
| **Temperature range (mobile)** | -25...+80 °C, (+105 °C. at max. 10 000 operating hours) |
| **Bend radius (fixed)** | 5× outer Ø |
| **Bend radius (moving)** | 10× outer Ø |
| **No. of bending cycles (C-track)** | 5 Mio. (25 °C) |
| **Acceleration (C-track)** | Max. 5 m/s |



The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

# Product Data Sheet

## Sensors and Actuator

| | |
|---|---|
| **Torsion stress** | ±180°/m |
| **No. of torsion cycles** | max.2 Mio(25°c) |
| **Torsion speed** | 35 cycle/min |

| **Approvals** |
|---|
| UL |
| CE |
| cULus |
| RoHS |

Note: This product has been manufactured by the following Class-I, Class-II and class-III **IPC** standards

**To understand the MPN please refer the below Table**

| **248-67-144-334-XXXX** | |
|---|---|
| 24 | Series |
| 8 | M8 connector |
| 6 | Female |
| 7 | Angle 90° |
| 1 | A code |
| 4 | PVC shielded cable-black |
| 4 | 4 pole connector |
| 3 | 3 core cable |
| 34 | 0.34 mm² (Core size) |
| XXXX | Cable length as per customer requirement |



The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220 India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.